















## LEGS & FEET





FOOTPLATE COVERS			LEG HANGER CAP	HEEL LOOP COVER
Bolt-on cover with wood base fits standard adult footplates	Lightweight gel and foam cover with adhesive base fits standard adult footplates	Bolt-on center-mount footboard cover with wood base fits most manufacturers' regular size	Velcro® closure; covers all manufacturers' hangers when legrest is not in use	Velcro® closure; three gel section design enhances fit
				
GFPC □ 20.32 x 15.24 cm	GFPCA □ 20.32 x 15.24 cm	GFPCS □ 27.94 x 22.86 cm	LHC □ 13.97 cm	HLC3

LEG WRAP	KNEE PROTECTOR WRAP	LEG PROTECTOR PAD	CALF PANELS	
Velcro® closure; fits 70° swingaway footrests **	Knee protector wrap fits knee bend on fixed-frame manual chairs with 1.90 to 2.54-cm tubing	8.89 x 30.48-cm pad and hardware; fits 2.22 or 2.54-cm tubing legs	Single piece with third strap prevents downward slippage	Split panel allows use of swingaway legs without removal
			 Back	
LPW □ 6.35 x 24.13 cm	KPR □ 1.27-cm Gel	FLGP12 □ 30.48 cm	GHS □ fits 40.64 - 50.80-cm wide	GHS-2 □ fits 40.64 - 50.80-cm wide


KNEE PROTECTOR BUTTONS *			
For elevating legrests; 3.18-cm thick	For elevating legrests; 1.98-cm thick	For swingaway footrests; 3.18-cm thick	For swingaway footrests; 1.98-cm thick
			
KBE	KBET	KBM	KBMT
* NOTE: 10.16cm (4") diameter. Includes mounting hardware to interface with all manufacturers.			






\*\* Velcro® is a registered trademark of Velcro Industries B.V. Ltd.

## ARMS

ARM REST PAD	TRACK-MOUNT PROTECTIVE SURFACE	TUBULAR ARM COVER	TROUGH LINER
Bolt-on, wood base gel pad with neoprene nylon cover and plastic base guard	Wood base gel pad with LaBac®-style track mounting	Lightweight, zip-on, neoprene nylon cover	Velcro closure; fits Otto Bock troughs
			
310G □ 8.89 x 25.40 cm	310TMS □ 8.89 x 25.40 cm	TAC	OTLM □ 33.02 cm
312G □ 8.89 x 30.48 cm	312TMS □ 8.89 x 30.48 cm		OTLL □ 48.26 cm
314G □ 8.89 x 35.56 cm	314TMS □ 8.89 x 35.56 cm		
316G □ 8.89 x 40.64 cm	316TMS □ 8.89 x 40.64 cm		
212G □ 5.08 x 30.48 cm	212TMS □ 5.08 x 30.48 cm		

## PADS

STICK ON with NEOPRENE NYLON COVER		ADDUCTOR / ELBOW	
Egg Shape, Thickness 1.91 cm	Oval Shape, Thickness 0.95 cm	Wood base, T-nut, flat pad with neoprene nylon cover	Metal base, T-nut, Synergel Dimensions™ Gel, curved pad with removable cover
			
ESP □ 6.66 x 11.43 x 1.59 cm	34SP □ 7.62 x 10.16 cm	AEP □ 7.62 x 10.16 cm	DAEPC □ 10.16 x 10.16 cm
	48SP1 □ 10.16 x 20.32 cm		
	412SP □ 11.43 x 30.48 cm		

SEAT BELT		CRUTCH COVERS		
Two-piece; slips onto 5.08 cm-wide seat belts	Two-piece; Velcro® onto 5.08 cm-wide seat belts	Zippered closure; for forearm crutch grip handle, with 1.27-cm gel	Gel and Foam stretch-on fits top of all standard crutches (over existing foam)	Velcro® closure; for standard crutch handles
				
SBC □ Standard Adult	SBCV □ Standard Adult	FCZC	CTC	CRHC